

**hotflex®**  
Flexible tubular heater

**more than  
100  
different  
dimensions  
in stock**



**Stock range**  
**Ø 6.5 mm (230 V)**  
with threaded pins M2.5

| Stock ID | L [mm] | P [W] |
|----------|--------|-------|
| 6500300  | 300    | 350   |
| 6500350  | 350    | 400   |
| 6500400  | 400    | 500   |
| 6500450  | 450    | 600   |
| 6500500  | 500    | 650   |
| 6500550  | 550    | 700   |
| 6500600  | 600    | 800   |
| 6500650  | 650    | 850   |
| 6500700  | 700    | 900   |
| 6500750  | 750    | 1000  |
| 6500800  | 800    | 1100  |
| 6500850  | 850    | 1200  |
| 6500900  | 900    | 1300  |
| 6500950  | 950    | 1350  |
| 6501000  | 1000   | 1400  |
| 6501050  | 1050   | 1450  |
| 6501100  | 1100   | 1500  |

| Stock ID | L [mm] | P [W] |
|----------|--------|-------|
| 6501150  | 1150   | 1550  |
| 6501200  | 1200   | 1600  |
| 6501250  | 1250   | 1650  |
| 6501300  | 1300   | 1700  |
| 6501350  | 1350   | 1800  |
| 6501400  | 1400   | 1900  |
| 6501450  | 1450   | 2000  |
| 6501500  | 1500   | 2100  |

**Stock range**  
**Ø 8.0 mm (240 V\*)**  
with threaded pins M4

| Stock ID | L [mm] | P [W]           |
|----------|--------|-----------------|
| 6300400  | 400    | 795             |
| 6300425  | 425    | 850 <b>new</b>  |
| 6300450  | 450    | 910             |
| 6300475  | 475    | 970 <b>new</b>  |
| 6300500  | 500    | 1025            |
| 6300525  | 525    | 1090 <b>new</b> |
| 6300550  | 550    | 1145            |
| 6300575  | 575    | 1200 <b>new</b> |
| 6300600  | 600    | 1260            |
| 6300625  | 625    | 1320 <b>new</b> |
| 6300650  | 650    | 1380            |
| 6300675  | 675    | 1440 <b>new</b> |
| 6300700  | 700    | 1495            |
| 6300725  | 725    | 1550 <b>new</b> |
| 6300750  | 750    | 1615            |

| Stock ID | L [mm] | P [W]           |
|----------|--------|-----------------|
| 6300775  | 775    | 1670 <b>new</b> |
| 6300800  | 800    | 1730            |
| 6300825  | 825    | 1790 <b>new</b> |
| 6300850  | 850    | 1845            |
| 6300875  | 875    | 1900 <b>new</b> |
| 6300900  | 900    | 1960            |
| 6300925  | 925    | 2020 <b>new</b> |
| 6300950  | 950    | 2080            |
| 6300975  | 975    | 2140 <b>new</b> |
| 6301000  | 1000   | 2195            |
| 6301025  | 1025   | 2260 <b>new</b> |
| 6301050  | 1050   | 2316            |
| 6301075  | 1075   | 2370 <b>new</b> |
| 6301100  | 1100   | 2430            |
| 6301125  | 1125   | 2480 <b>new</b> |
| 6301150  | 1150   | 2545            |
| 6301175  | 1175   | 2600 <b>new</b> |

| Stock ID | L [mm] | P [W]           |
|----------|--------|-----------------|
| 6301200  | 1200   | 2665            |
| 6301225  | 1225   | 2730 <b>new</b> |
| 6301250  | 1250   | 2780            |
| 6301275  | 1275   | 2840 <b>new</b> |
| 6301300  | 1300   | 2895            |
| 6301325  | 1325   | 2960 <b>new</b> |
| 6301350  | 1350   | 3015            |
| 6301375  | 1375   | 3070 <b>new</b> |
| 6301400  | 1400   | 3130            |
| 6301425  | 1425   | 3180 <b>new</b> |
| 6301450  | 1450   | 3245            |
| 6301475  | 1475   | 3300 <b>new</b> |
| 6301500  | 1500   | 3365            |
| 6301525  | 1525   | 3420 <b>new</b> |
| 6301550  | 1550   | 3480            |
| 6301575  | 1575   | 3530 <b>new</b> |
| 6301600  | 1600   | 3600            |

**Stock range**  
**Ø 8.5 mm (230 V)**  
with threaded pins M2.5

| Stock ID | L [mm] | P [W]           |
|----------|--------|-----------------|
| 6100300  | 300    | 650             |
| 6100350  | 350    | 750             |
| 6100375  | 375    | 825 <b>new</b>  |
| 6100400  | 400    | 900             |
| 6100425  | 425    | 975 <b>new</b>  |
| 6100450  | 450    | 1050            |
| 6100475  | 475    | 1100 <b>new</b> |
| 6100500  | 500    | 1150            |
| 6100525  | 525    | 1225 <b>new</b> |
| 6100550  | 550    | 1300            |
| 6100575  | 575    | 1375 <b>new</b> |
| 6100600  | 600    | 1450            |
| 6100625  | 625    | 1525 <b>new</b> |
| 6100650  | 650    | 1600            |

| Stock ID | L [mm] | P [W]           |
|----------|--------|-----------------|
| 6100675  | 675    | 1675 <b>new</b> |
| 6100700  | 700    | 1750            |
| 6100725  | 725    | 1825 <b>new</b> |
| 6100750  | 750    | 1900            |
| 6100775  | 775    | 1975 <b>new</b> |
| 6100800  | 800    | 2050            |
| 6100825  | 825    | 2125 <b>new</b> |
| 6100850  | 850    | 2200            |
| 6100875  | 875    | 2275 <b>new</b> |
| 6100900  | 900    | 2350            |
| 6100925  | 925    | 2425 <b>new</b> |
| 6100950  | 950    | 2500            |
| 6100975  | 975    | 2575 <b>new</b> |
| 6101000  | 1000   | 2650            |

| Stock ID | L [mm] | P [W]           |
|----------|--------|-----------------|
| 6101025  | 1025   | 2725 <b>new</b> |
| 6101050  | 1050   | 2800            |
| 6101075  | 1075   | 2865 <b>new</b> |
| 6101100  | 1100   | 2930            |
| 6101150  | 1150   | 3060            |
| 6101200  | 1200   | 3190            |
| 6101250  | 1250   | 3320            |
| 6101300  | 1300   | 3450            |
| 6101350  | 1350   | 3580            |
| 6101400  | 1400   | 3710            |
| 6101450  | 1450   | 3840            |
| 6101500  | 1500   | 3970            |

**Stock range**  
**Ø 8.5 mm (230 V)**  
with threaded pins M2.5

| Stock ID | L [mm] | P [W] |
|----------|--------|-------|
| 6110500  | 500    | 700   |
| 6110550  | 550    | 780   |
| 6110600  | 600    | 860   |
| 6110650  | 650    | 950   |
| 6110700  | 700    | 1000  |
| 6110750  | 750    | 1100  |
| 6110800  | 800    | 1190  |

| Stock ID | L [mm] | P [W] |
|----------|--------|-------|
| 6110850  | 850    | 1250  |
| 6110900  | 900    | 1350  |
| 6110950  | 950    | 1430  |
| 6111000  | 1000   | 1500  |
| 6111050  | 1050   | 1590  |
| 6111100  | 1100   | 1650  |
| 6111150  | 1150   | 1750  |
| 6111200  | 1200   | 1830  |
| 6111250  | 1250   | 1900  |
| 6111300  | 1300   | 1990  |
| 6111350  | 1350   | 2070  |
| 6111400  | 1400   | 2150  |
| 6111450  | 1450   | 2230  |
| 6111500  | 1500   | 2300  |

\* with connection voltage 230 V wattage will decrease by 8%.